



# Opal Shower On Bracket With Air Shower II

# Nero



Versions:202401

## Drawing



## Specifications

### Watermark License

WM-060093

### Temperature Rating

Min 1°C-Max 75°C

### Pressure Rating

Min 150kpa - Max 500kpa

## Finish & SKU

- |  |  |
|--|--|
|  <b>Brushed Bronze</b><br>NR251905fBZ |  <b>Brushed Nickel</b><br>NR251905fBN |
|  <b>Graphite</b><br>NR251905fGR       |  <b>Brushed Gold</b><br>NR251905fBG   |

## Packaging Includes

- 1x Hand Shower ( Built- In Check Valve)
- 1x Shower Bracket
- 1x 1.5m PVC Hose

\*Dimensions are nominal measurements only.


## Important

All products must be installed by licensed plumbers.

All pipework must be thoroughly flushed prior to installation, as foreign materials may block the flow regulating device and reduce the flow of water.




1. Apply thread sealant or teflon tape on outlet thread.




2. Pull back plate on together with bracket body.

Apply thread sealant or teflon tape



3. Screw shower bracket body on to outlet. **DO NOT OVERTIGHTEN.** Slide the back plate against the wall/tile face properly.



4. Connect bracket and hand shower with hose. **TEST & CHECK FOR LEAKS.**

# Nero

info@nerotapware.com.au  
nerotapware.com.au

11-13 Buontempo Road  
Carrum Downs Vic 3201

